

Field Tile Sizes



**Sand - SAN**  
NORMATSAN1224 - 12"x24" Rectified Field Tile - Matte  
NORMATSAN3232 - 32"x32" Rectified Field Tile - Matte



**Silver - SIL**  
NORMATSIL1224 - 12"x24" Rectified Field Tile - Matte  
NORMATSIL3232 - 32"x32" Rectified Field Tile - Matte



**Greige - GRE**  
NORMATGRE1224 - 12"x24" Rectified Field Tile - Matte  
NORMATGRE3232 - 32"x32" Rectified Field Tile - Matte



**Mud - MUD**  
NORMATMUD1224 - 12"x24" Rectified Field Tile - Matte  
NORMATMUD3232 - 32"x32" Rectified Field Tile - Matte

3" Hexagon Mosaic - Matte (10 1/4"x11 3/4" Sheet)



**Sand - SAN**  
NORMATSAN3HEXMO



**Silver - SIL**  
NORMATSIL3HEXMO



**Greige - GRE**  
NORMATGRE3HEXMO



**Mud - MUD**  
NORMATMUD3HEXMO



# Materika

## Glazed Color Body Porcelain


Photo Features 32"x32" Rectified Field Tile - Matte in Sand.

### SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		NORMAT...1224	12"x24"	Rectified Field Tile - Matte	6	3
		NORMAT...3232	32"x32"	Rectified Field Tile - Matte	2	8
Trim		NORMAT...3X24BN	3"x24"	Bullnose - Matte	15	-
Mosaic		Ø NORMAT...3HEXMO	10 1/4"x113/4" Sheet	3" Hexagon Mosaic - Matte	6	5.04


### ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	N/A	Unaffected	N/A	Pass (1,300 ISO)	≤0.5%	Unaffected



### APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻




### LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- \* Special Order only



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COM/IGG UL 2818



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

