Bedrosians[®]

12"x24" Field Tile - Matte





Argent - ARG



Noir - NOI 100000695



24"x48" Field Tile - Matte

Bone - BON 100000178

Bone - BON

100000694

24"x48" Parallelo Deco Tile - Matte



Argent - ARG 100000175



Noir - NOI 100000179



Bone - BON 100000181



Argent - ARG 100000180



Noir - NOI 100000182

1"x4" Straight Set Mosaic - Matte (12"x12" Sheet)



Bone - BON 100000190



Argent - ARG

bedrosians.com



Noir - NOI 100000191



SIZING & PACKAGING

Туре	Shape		Argent Code	Bone Code	Noir Code	Size	Description	Pcs/Ctn	Sf/Ctn
Field			100000693	100000694	100000695	12"x24"	Rectified Field Tile - Matte	7	13.24
			100000175	100000178	100000179	24"x48"	Rectified Field Tile - Matte	2	15.28
			100000180	100000181	100000182	24"x48"	Rectified Parallelo Deco Tile - Matte	2	15.28
Trim			100000185	100000187	100000188	3"x24"	Bullnose - Matte	10	-
Mosaic		Ø	100000189	100000190	100000191	12"x12" Sheet	1"x4" Mosaic - Matte	5	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM#C650
Results	≥0.42	5	Unaffected	5	Pass (1,300 ISO)	≤0.5%	Unaffected

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	٠	۲	۲	٠	•	٠
Commercial	٠	۲	٠	٠	●	٠

LEGEND

Ø

Product rated for Interior & Exterior use

• Product rated for Interior use only Applications & ANSI Technical Specifications do not apply







* Special Order only

P



† May be suitable for Exterior Floors



33% Overlap should not exceed 33%

Shade Variation

V2-Slight

Minimum 3/16" Grout Joint

Use of a leveling system during installation is strongly recommended

It is recommended to install deco tiles without an offset.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.



