

# AURA

Aura mixes a natural surface with a thin layer of color, giving the sense of an impressionist painting with a hint of metal peeking through. A member of our Metallics Collection, Aura is available in Green, Beige, or Blue tones and stocked in 24" x 24" porcelain field tiles.





# AURA



Blue Matte



Beige Matte



Green Matte



Blue Matte



Beige Matte



Green Matte

APPLICATIONS								ATTRIBUTES	VARIATION
INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	DCOF <sup>2</sup>	
Medium Traffic Commercial	All	Yes, including steam	Yes <sup>1</sup>	No	Yes, including freeze thaw	Yes, non-freeze thaw	Yes	0.62 0.67 0.66	

INSTALLATION/MAINTENANCE									
SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT
Ardex X7 Microtec Fiber Reinforced Mortar <sup>3</sup>	Ardex FL Rapid Set Sanded <sup>4</sup>	1/8" minimum	Ardex 8+9	Ardex SX	AquaMix Grout Release	AquaMix Concentrated Stone & Tile Cleaner	TCNA Handbook	33% max. offset	Sample <sup>5</sup>

**RECTIFIED FIELD TILE**

24" x 24" x 3/8"  
Matte

NOTES
<sup>1</sup> Mosaic formats only
<sup>2</sup> The standard requires a minimum wet DCOF Acutest value greater than 0.42 for ceramic tiles (inclusive of porcelain) for level interior spaces expected to be walked upon when wet.
<sup>3</sup> Alternate mortar - Ardex X5 Medium Bed Mortar or Mapei Ultraflex LFT
<sup>4</sup> Alternate grout - Mapei Flexcolor CQ or Mapei Ultracolor Plus FA
<sup>5</sup> Layout for overview of material before installation.
30 faces
Tech Note: Porcelains that meet the DCOF standard may have a more abrasive surface that might show dirt or debris. Remove with soap, water and firm scrubbing in order to clean. Consider this in the selection process.