Available Sizes



TRVDURANGO1818FH - 18"x18" Filled & Honed Bevel TRVDURANGO1836B - 18"x36" Brushed Straight Edge TRVDURANGO2424FH - 24"x24" Filled & Honed Bevel



TRVDURANGO312B - 3"x12" Brushed Straight Edge



TRVDURANGOPAVSET - 3cm Paver Set - Tumbled (16 s/f set) TRVDURANGO1224PC5 - 24"x24" 3cm Paver - Tumbled



TRVDURANGOBUNDLE Versailles Pattern Bundle - Filled & Honed (8 sq ft per bundle)




SIZING & PACKAGING

Туре	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TRVDURANGO312B	3"x12"	Field Tile - Brushed Straight Edge	-	-
		TRVDURANGO1818FH	18"x18"	Field Tile - Filled & Honed Bevel	-	-
		TRVDURANGO1836B	18"x36"	Field Tile - Brushed Straight Edge	-	-
		TRVDURANGO2424FH	24"x24"	Field Tile - Filled & Honed Bevel	-	-
		TRVVERSND1818FH	8 sq.ft. bundle	Versailles Pattern Bundle - Filled Light Chiseled - Brushed	-	-
Trim		TRVDURANGOCANEH	9/16"x3/4"x12"	Cane - Honed	-	-
		TRVDURANGOCHAIRH	2"x12"	Chair Rail - Honed	-	-
Mosaic		TRVDURANGOHEXH	12"x12" Sheet	2" Hex Mosaic- Honed Straight Edge	-	-
Paver		TRVDURANGOPAVSET	16 s/f Set	3cm Paver Set - Tumbled	-	-
		TRVDURANGO1224PC5	12"x24"	5cm Eased Edge Pool Coping - Tumbled	-	-
		TRVDURANGO1624PC5	16"x24"	5cm Eased Edge Pool Coping - Tumbled	-	-
		TRVDURANGO2424PC3	24"x24"	3cm Paver-Tumbled	-	-

APPLICATIONS

	Floors (Textured Only)	Walls	Countertops	Shower Floors (Textured & Small Mosaics Only)	Shower Walls	Pools/Spas
Residential	• †	•	•	• †	•	
Commercial	• †	•	•	• †	•	





LEGEND

Product rated for Interior & Exterior use

Applications & ANSI Technical Specifications do not apply

- Product rated for Interior use only
 - * Special Order only

† May be suitable for Exterior Floors



[†] The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks or ramps. No polished tiles; only textured surfaces may be suitable.

Since travertine is a capillary filled stone, foot traffic or high pressure items may expose these voids. To remedy, seal the surrounding area and fill the hole with sanded or epoxy grout in a color that matches the stone. Then re-seal the stone.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Natural stone has inherent variation in color/shade, size, texture, finish, veining, grain, movement and pitting. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Ensure proper installation, application, use, care and maintenance. Natural stone must be sealed prior to installation. Do not use aerosol catalyst adhesives. Only use pH neutral cleaners. Natural stone may experience changes in color and finish if installed in an exterior application. There is no warranty for natural stone. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

