
Bedrosians® Tile & Stone

Glazed Porcelain/Ceramic

Wall Tile Sizes



100000803 - 2 3/4"x11" Non-Rectified Wall Tile - Glossy 100000799 - 2 3/4"x11" Non-Rectified Wall Tile - Matte



lvory 100000804 - 23/4"x11" Non-Rectified Wall Tile - Glossy 100000800 - 23/4"x11" Non-Rectified Wall Tile - Matte



Grey 100000805 - 23/4"x11" Non-Rectified Wall Tile - Glossy 100000801 - 2 3/4"x11" Non-Rectified Wall Tile - Matte



100000802 - 23/4"x11" Non-Rectified Wall Tile - Matte

Noir 100000806 - 23/4"x11" Non-Rectified Wall Tile - Glossy

1/2"x12" Jolly Trim - Glossy and Matte

White 100000811 - Glossy 100000807 - Matte Ivory 100000812 - Glossy 100000808 - Matte

100000813 - Glossy 100000809 - Matte

Noir 100000814 - Glossy 100000810 - Matte



SIZING & PACKAGING

Type	Shape		Grey	lvory	Noir	White	Size	Description	Pcs/Ctn	Sf / Ctn
Wall		Ø	100000805	100000804	100000806		23/4"x11"	Non-Rectified Wall Tile - Glossy	27	5.70
		Ø				100000803	23/4"x11"	Non-Rectified Wall Tile - Glossy	30	6.35
			100000801	100000800	100000802	100000799	23/4"x11"	Non-Rectified Wall Tile - Matte	30	6.35
Trim		Ø	100000813	100000812	100000814	100000811	1/2"x12"	Jolly Trim - Glossy	50	-
		Ø	100000809	100000808	100000810	100000807	1/2"x12"	Jolly Trim - Matte	50	_

ANSITECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	4	Unaffected	4	≥ 400 lbf	≤0.5%	Unaffected

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•	•	•	•	•
Commercial	•	•	•	•	•	•

LEGEND

Product rated for Interior & Exterior use

Applications & ANSI Technical Specifications do not apply

- Product rated for Interior use only
 - * Special Order only

Shade Variation



V1-Uniform









Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

† May be suitable for Exterior Floors