

White Carrara and Thassos



100001357  
Mosaic 1 Blend - Honed  
(11 1/4"x11 1/4" Sheet)



100001368  
Mosaic 2 Blend - Honed  
(12 1/8"x12 1/8" Sheet)



100001373  
Mosaic 3 Blend - Honed  
(12 1/8"x12 1/8" Sheet)



100001376  
Mosaic 4 Blend - Honed  
(10 1/2"x12" Sheet)


White Carrara and Nero Marquina



100001356  
Mosaic 1 Blend - Honed  
(11 1/4"x11 1/4" Sheet)



100001367  
Mosaic 2 Blend - Honed  
(12 1/8"x12 1/8" Sheet)



100001372  
Mosaic 3 Blend - Honed  
(12 1/8"x12 1/8" Sheet)



100001375  
Mosaic 4 Blend - Honed  
(10 1/2"x12" Sheet)



# Matisse

Decorative (Marble Blend Mosaics)

Photo Features Mosaic 2 Blend - Honed in White Carrara and Nero Marquina.


## SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Mosaic		100001375	10 1/2"x12" Sheet	Mosaic 4 Blend - Honed in White Carrara & Nero Marquina	5	4.38
		100001376	10 1/2"x12" Sheet	Mosaic 4 Blend - Honed in White Carrara & Thassos	5	4.38
		100001356	11 1/4"x11 1/4" Sheet	Mosaic 1 Blend - Honed in White Carrara & Nero Marquina	5	4.39
		100001357	11 1/4"x11 1/4" Sheet	Mosaic 1 Blend - Honed in White Carrara & Thassos	5	4.39
		100001367	12 1/8"x12 1/8" Sheet	Mosaic 2 Blend - Honed in White Carrara & Nero Marquina	5	5.10
		100001368	12 1/8"x12 1/8" Sheet	Mosaic 2 Blend - Honed in White Carrara & Thassos	5	5.10
		100001372	12 1/8"x12 1/8" Sheet	Mosaic 3 Blend - Honed in White Carrara & Nero Marquina	5	5.10
		100001373	12 1/8"x12 1/8" Sheet	Mosaic 3 Blend - Honed in White Carrara & Thassos	5	5.10

## ANSI TECHNICAL SPECIFICATIONS

	Abrasion Resistance	Water Absorption	Average Bulk Specific Gravity	Compressive Strength Perpendicular (Dry)	Flexural Strength Perpendicular (Dry)	Modulus Rupture Perpendicular (Dry)
Results	11.98lw	0.16	167.28 lbs/ft <sup>3</sup> 2,680.6 kg/m <sup>3</sup>	13,000 psi	1,340 psi	1,500 psi

### Shade Variation



## APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	☐	☐	● †	☐	
Commercial	● †	☐	☐	● †	☐	

## LEGEND

- ☐ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- \* Special Order only

Please be aware that white stones installed on shower floors may experience oxidization and rusting.

All natural stone products must be sealed prior to grouting.

Do not use chlorine, acids, or other harsh chemicals to clean. All spills must be cleaned immediately to prevent staining.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Natural stone has inherent variation in color/shade, size, texture, finish, veining, grain, movement and pitting. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Ensure proper installation, application, use, care and maintenance. Natural stone must be sealed prior to installation. Do not use aerosol catalyst adhesives. Only use pH neutral cleaners. Natural stone may experience changes in color and finish if installed in an exterior application. There is no warranty for natural stone. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

